

CleanMatic

HIGH PRESSURE CLEANER
NETTOYEUR HAUTE PRESSION
HOCHDRUCKREINIGER
HIDROLIMPIADORA ALTA PRESIÓN
LAVADORA A ALTA PRESSÃO
ГИДРОМОЙКА ВЫСОКОГО ДАВЛЕНИЯ
IDROPULITRICE AD ALTA PRESSIONE



- OPERATING INSTRUCTIONS
- MODE D'EMPLOI
- BEDIENUNGSANLEITUNG
- INSTRUCCIONES PARA EL USO
- MANUAL DE INSTRUÇÕES
- ИНСТРУКЦИЯ ПО ЭКСПЛУАТАЦИИ
- LIBRETTO ISTRUZIONI



- DO NOT USE THE MACHINE WITHOUT FIRST READING THE OPERATING INSTRUCTIONS
- N'UTILISER L'APPAREIL QU'APRÈS AVOIR LU LE MANUEL D'INSTRUCTIONS
- GERAT ERST NACH LESEN DER BEDIENUNGSANLEITUNG VERWENDEN
- NO UTILISE EL APARATO SIN LEER ANTES LAS INSTRUCCIONES PARA SU USO
- NÃO USE A MÁQUINA SEM LER A MANUAL DE INSTRUÇÕES
- НЕ ИСПОЛЬЗУЙТЕ УСТРОЙСТВО, НЕ ПРОЧИТАВ СНАЧАЛА ИНСТРУКЦИЮ ПО ЭКСПЛУАТАЦИИ
- NON USARE LA MACCHINA SENZA AVERE LETTO LE ISTRUZIONI PER L'USO

2 - TECHNICAL DATA

MODEL		CL 22	CL 24	CL 10	CL 11	CL 26
Volume		7 l/min. 1.8 gpm	7 l/min. 1.8 gpm	7 l/min. 1.8 gpm	1.85 G.P.M. (USA)	7 l/min. 1.8 gpm
Equivalent washing impact of the jet with Rotoclean	bar	E.W. bar / MPa / psi: specific pressure of the jet, in bar / MPa / P.S.I.				
	MPa	160	160	150	160	160
	P.S.I.	2320	2320	2175	2320	2320
Max Working pressure	bar	90	90	80	90	90
	MPa	9	9	8	9	9
	P.S.I.	1300	1300	1160	1300	1300
Reaction thrust of the jet (recoil)		< 20 N	< 20 N	< 20 N	< 20 N	< 20 N
Admissible peak overpressure	bar	120	120	110	120	120
	MPa	12	12	11	12	12
	P.S.I.	1750	1750	1600	1750	1750
Singlephase motor power	kW.	1,75	1,75	1,6	1,75	1,75
	V.	230	240	100	120	208÷230
	Hz.	50	50	60	60	60
	A.	7,5	7,5	15	15	7,5
Motor protector		Current thermal overload				
Motor protection grade		IPX5				
Noise level *		Lp dB(A) 74 (uncertainly 1,5) - Lw dB(A) 90				
Lance vibration *	m/sec ²	Fixed nozzle A(8) than 2,5 -Rotating nozzle A(8) 5 (uncertainly 1)				
Max. inlet water temperature		60° C - 140° F				
Max suction depth		1 mt - 3,3 ft				
Max inlet pressure	bar	10				
	MPa	1				
	P.S.I.	145				
Hose length	7 m. 23 ft.	Thermoplastic material reinforced with nylon braid internal diameter 1/4" Maximum working pressure 140 bar - 14 MPa - 2030 psi				
Mass		with trolley: Kg 12,2 - lbs 26,9 without trolley: Kg 11,4 - lbs 25,1				
Dimensions with trolley		mm 520 x 225 x 360 (h) - inches 20,5 x 8,8 x 14,1 (h)				
Dimensions without trolley		mm 390 x 180 x 300 (h) - inches 15,3 x 7 x 11,8 (h)				

* (Reference Standard EN60335-2-79).