



PA



PA3 150



PA2 80-100



PA1 70

65
dB

IT. Elettropompa per Gasolio

Elettropompe rotative autoadescanti di tipo volumetrico a palette per il travaso di gasolio. Sono equipaggiate con motore elettrico asincrono a induzione auto-ventilato con grado di protezione IP55, classe di isolamento tipo F, con termica di protezione da sovraccarico inserita nell'avvolgimento. Tutti i modelli sono dotati di valvola by pass e filtro in acciaio inox incorporati nella pompa. Corpo in ghisa con trattamento di verniciatura anti-corrosione; girante in acciaio sinterizzato e palette in acetilica. Pompe robuste che garantiscono affidabilità e durata nel tempo.

Caratteristiche	70	80	100	150
• portata	70 l/min	80 l/min	100 l/min	150 l/min
• entrata/uscita	1" BSP-G	1" BSP-G	1" BSP-G	1" BSP-G
• fluidi	diesel	diesel	diesel	diesel

Opzioni

- spina australiana, americana, inglese, brasiliana
- filettatura entrata-uscita NPT
- kit antisifone
- motore 115V su richiesta

EN. Electric pumps for Diesel

Self-priming volumetric vane pumps for transferring diesel fuel. The pumps are equipped with asynchronous electric self-ventilated induction engine with protection rating IP55, F type insulation class, with thermal overload protection inserted in the coil. All models are equipped with built-in by-pass valve and stainless steel filter. Cast iron body with anti-corrosion coating; sintered steel rotor and acetal resin vanes. Sturdy pumps that ensure reliability and long service life.

Features	70	80	100	150
• flow rate	70 l/min	80 l/min	100 l/min	150 l/min
• in/out	1" BSP-G	1" BSP-G	1" BSP-G	1" BSP-G
• fluids	diesel	diesel	diesel	diesel

Options

- Australian, American, English, Brazilian socket
- NPT inlet/outlet threads
- anti-siphon kit
- upon request 115V engine



ciclo di lavoro CONTINUO 70L
CONTINUOUS duty cycle 70L



ciclo di lavoro - duty cycle



motore - engine