

ROYAL PRESS (BY-PASS MODEL)

PRESSURE

200 bar

FLOW RATE

1000 l/h

ENGINE POWER

7 kW



EXCLUSIVE CHARACTERISTICS

- ▶ BY-PASS - BYP
- ▶ THERMOSTATIC VALVE - TSV

MOST FREQUENTLY USE

AUTOMOTIVE

AGRICULTURE

CONSTRUCTION INDUSTRY

MUNICIPALITIES

HEAVY INDUSTRY

INNOVATIONS



SPECS



LARGE DIAMETER WHEELS TO FACILITATE MOVEMENT.



STURDY PAINTED STEEL FRAME.



THERMOSTATIC VALVE TO PROTECT THE PUMP FROM OVERTEMPERATURE WHILE LEFT IN BY-PASS PHASE.

TECHNICAL DATA

		ROYAL PRESS 3060 T
Code		IDAF39334
PERFORMANCE		
Operating pressure max	bar/Mpa	30-200/3-20
Flow rate	l/h	480-1000
Inlet water max. temperature	°C	50
Power supply	Ph-V-Hz/A	3-415-50/12,5
Absorbed power	kW	7
Motor pole/rpm		4-1400
Remote control		BYP
Pump/head/pistons		Plunger/brass/ceramic
Detergent tank	l	5
Detergent delivery		low pressure
Dimension (LxWxH)	cm	77x51x87
Weight	kg	67

STANDARD EQUIPMENT

CODE: IPPR40020 HANDGRIP G6000	CODE: LCPR89117 EXTENSION PD70 0°	CODE: UGLN49987 H.P. NOZZLE Ø 15045	CODE: UGLN05174 L.P. NOZZLE Ø 5040	CODE: TBAP25324 HIGH PRESSURE HOSE 10 m

OPTIONAL ACCESSORIES

CODE: RCIN10810 HOSE COUPLINGS M22	CODE: SPID24911 HYDRO BRUSH LANCE	CODE: TBAP23853 DRAIN KIT 10 m	CODE: TBAP24406 DRAIN KIT 20 m	CODE: LCPR40040 FOAMER KIT 1 l
CODE: LCPR14858 SANDBLASTER KIT Ø 1,4	CODE: PRCH40041 SAND BAG 25 kg	CODE: LCPR40135 ROTATING LANCE TPR255 0,45	CODE: KTRI29366 PLUNGED EJECTOR DEVICE	