



High Pressure Cleaner



Model	IDS-3032	IDS-3082	IDS-3082
Flow Rate (L/min) GRM	(12) 3.15	(18) 5	(18) 5
Maximum Pressure (bar/psi)	130 / 1900	200 / 2900	200 / 2900
Power Source	Direct Coupled	Belt Driven	Belt Driven
Engine	Robin EY-20D	Honda GX-390	Atlanta CF-186F
Engine Type	Air-cooled Gasoline	Air-cooled Gasoline	Air-cooled Diesel
Max. Output (hp/rpm)	5 / 3600	13 / 3600	10 / 3600
Starting System	Recoil	Recoil	Recoil
Dimensions (L x W x H) (mm)	600 x 450 x 500	800 x 520 x 700	800 x 590 x 700

Sludge Pump

TSLP-150 6 inch Sludge Pump specially designed to handle clean or dirty water containing limited solids, and mostly use extensively on construction sites for dewatering.

TSLP-150 is automatic priming and re-priming, is by flood alubricating rotary sliding vane vacuum pump.

- High capacity water pump, used for WellPoint dewatering and sump pumping.
- Hard wearing cast iron parts.
- Automatic priming.
- High airflows vacuum system specially designed for dewatering works.
- Hours of unattended operation or intermittent flow.
- Large fuel tank capacity of 140 liters for continuous operation.
- Lifting Hook.
- Key start Engine.
- Available option four wheel site trailer.



Model	TSLP-150
Type	Self-priming Centrifugal
Suction x Delivery Diameter (inch)	6" x 6"
Total Head (m)	33
Max. Flow (liter/second)	87
Axle Seal Material	Mechanical Seal (Ceramic-carbon)
Suction m(ft)	8 (26)
Engine / Engine Type	Beinei F3L912 / Air-cooled Diesel
Max. Output (hp/rpm)	32 / 1500
Starting System	Electric Start
Weight (kg)	960
Dimension (L x W x H) (mm)	2000 x 1200 x 1650